



SA 2000+ COLD BOND CEMENT & HARDENER

SA 2000+ is designed to be a fast curing cement for returning a lagged pulley to service safely. It is ideal for bonding rubber to steel, rubber to rubber, rubber to fabric and fabric to fabric. It will also bond wood, fiberglass, concrete and urethane.

FEATURES

- SA 2000+ is a chloroprene based cement and is available in four sizes
- Non-flammable
- High initial and permanent adhesion
- Mixed in 9 Almix locations globally

SA 2000+ HARDENER

PRODUCT CODE	GRAM	OUNCE
CH-SA2000+-055	55	1.94

SA 2000+ COLD BOND CEMENT

PRODUCT CODE	WEIGHT		COVERAGE		HARDENER BOTTLE QUANTITY
	KG	LBS	M ²	FT ²	
CC-SA2000+-002	1	2.2	3.7	40	1 CH-SA2000+-055
CC-SA2000+-010	5	11	18.6	200	5 CH-SA2000+-055
CC-SA2000+-200	290	640	1,078	11,600	290 CH-SA2000+-055

SA 2000+ PROPERTIES	
Pot Life	2 Hours @ 21 °C / 70 °F
Working Temperature	-40 °C to 82 °C / -40 °F to 180 °F
Shelf Life	24 months in a cool, dark location



Note: The above data is based on extensive testing and represents standard values. Shaw Almix Industries reserves the right to make changes without prior notice and refuses all claims arising from such changes. All items are subject to change without previous notice.