



Nominal outer inner \emptyset	Recommended usage range Hose diameter mm / approx. inch	Safeplast article no. for black coils	Safeplast article no. for yellow coils	Coil length	Weight average kg/m	Wall W mm	Pitch P mm	Hole \emptyset Z mm
12 / 9.6 mm (ID ~0.38")	9 – 13 0.35 – 0.51"	012R25MU	012R25KE	25 m	0.04	1.2	10	-
16 / 13.4 mm (ID ~0.52")	13 – 18 0.51 – 0.71"	016R25MU	016R25KE	25 m	0.06	1.3	12	-
20 / 16.0 mm (ID ~0.63")	16 – 22 0.51 – 0.71"	020R25MU	020R25KE	25 m	0.09	2.0	20	7
25 / 20.6 mm (ID ~0.81")	20 – 27 0.78 – 1.06"	025R25MU	025R25KE	25 m	0.15	2.2	21	7
32 / 27.0 mm (ID ~1.06")	27 – 36 1.06 – 1.42"	032R25MU	032R25KE	25 m	0.19	2.5	22	7
40 / 34.6 mm (ID ~1.36")	34 – 44 1.34 – 1.73"	040R25MU	040R25KE	25 m	0.30	2.7	24	7
50 / 43.2 mm (ID ~1.70")	43 – 55 1.69 – 2.16"	050R25MU	050R25KE	25 m	0.40	3.4	30	7
63 / 55.6 mm (ID ~2.19")	55 – 67 2.16 – 2.64"	063R25MU	063R25KE	25 m	0.65	3.7	37	10
75 / 66.2 mm (ID ~2.60")	66 – 80 2.60 – 3.15"	075R20MU	075R20KE	20 m	0.73	4.4	42	10
90 / 80.2 mm (ID ~3.16")	80 – 98 3.15 – 3.86"	090R15MU	090R15KE	15 m	1.20	4.9	45	10
110 / 99.0 mm (ID ~3.90")	99 – 115 3.90 – 4.53"	110R10MU	110R10KE	10 m	1.76	5.5	50	10
125 / 113.2 mm (ID ~4.46")	113 – 130 4.45 – 5.12"	125R8MU	125R8KE	8 m	2.05	5.9	52	10
140 / 127.0 mm (ID ~5.00")	125 – 155 4.92 – 6.10"	1406000MU	1406000KE	6 m	2.50	6.5	55	10